

B/W Dome Camera

Products List > A Series > Camera > B/W Dome Camera > MTC-908D, MTC-906D

MTC-908D, MTC-906D

FEATURES

Black or Ivory Finish Available



MTC-908D



MTC-906D




MTC-908D

- ◆ 1/3" Hi-Res.
- ◆ B/W Dome Camera
- ◆ 600TVL/ 0.05Lux@F2.0
- ◆ 12Vdc

MTC-906D

- ◆ 1/3" Med-Res.
- ◆ B/W Dome Camera
- ◆ 450TVL/ 0.05Lux@F2.0
- ◆ 12Vdc



Tol: ±0.5 Unit:mm

SPECIFICATIONS

	MTC-908D		MTC-906D	
TV System	CCIR	EIA	CCIR	EIA
Image Sensor	1/3" Sony B/W CCD			
Number of Total Pixels	753(H)x582(V)	771(H)x492(V)	537(H)x597(V)	537(H)x505(V)
Resolution	600TVL		450TVL	
Minimum Illumination	0.05Lux@F2.0			
Video Output ; Connector	1.0Vp-p Composite, 75Ω ; BNC			
Signal to Noise Ratio	More than 48dB			
Gamma Correction	0.45			
Synchronizing System	Internal			
Automatic Electronic Shutter	ON:1/50(60)sec.~1/100,000sec. / OFF:1/50(60)sec.			
Automatic Gain Control	Automatic			
Automatic White Balance	NA			
Back Light Compensation	Automatic			
Flickerless	NA			
DNR ; Sense Up	NA			
Digital Day&Night Mode	NA			
Automatic IRIS	NA			
Adjustment VR	NA			
Lens Mount	Built-in Board Lens			
Lens, Angle of View(H)	Standard:f3.6mm/F2.0/72.5° Option:f2.5mm/105°, f2.9mm/90°, f6.0mm/47.5°, f8.0mm/36.5°, f12.0mm/24.5°, f16.0mm/17.5°			
Power Supply ; Consumption	12Vdc ; 1.2W			
Operation ; Storage Temp.	-10°C~50°C ; -20°C~60°C			
Operation ; Storage Humidity	Maximum:RH80% ; RH90%			
Dimensions	112(DIA)x70(H)mm			
Net Weight	220g			
Accessories Series Option(Page)	NA			